

# An asymptotic preserving and well-balanced scheme for the M1 model for radiative transfer

**Hélène BLOCH**, Maison de la Simulation

**Pascal TREMBLIN**, Maison de la Simulation

**Edouard AUDIT**, Maison de la Simulation

**Matthias GONZÁLEZ**, AIM

The problem of radiative transfer describes the interaction between light and matter, therefore it appears in many physical situations, such as astrophysical systems, laser matter interactions, or atmospheric physics [1]. Instead of solving a complex equation in a seven dimensional space, one can use a moment model by averaging over the direction of propagation to follow the radiative energy, flux, pressure, etc in a five dimensional space. By using a closure relation expressing the radiative pressure as a function of radiative energy and flux, one can derive the M<sub>1</sub> model [2, 3] that is able to accurately capture the two main regime in radiative transfer: optically thin medium in which photons are free streaming and the optically thick medium in which photons are constantly interacting and obey a diffusion equation in the asymptotic limit [4].

At the discrete level, two major difficulties relating to the M<sub>1</sub> model come from the asymptotic behaviour and the capture of constant flux steady state that are difficult to capture by standard finite volume approaches. To deal with these issues, we propose an asymptotic preserving and well-balanced scheme. The Riemann fluxes on the radiative energy equations are corrected to get the asymptotic preserving property, and the whole scheme is also adapted to get the well-balanced property in either the diffusive and free-streaming limits for constant flux steady state. We present also first tests showing these properties of the proposed numerical scheme.

A time explicit scheme would be limited by the speed of light, therefore a time implicit solver is used. Linear systems are solved using the library Trilinos. The implementation is done using the code ARK developed in [5] in order to achieve high performance computing and portability across different architectures (e.g. multi-core, many-core, GP-GPU).

## Références

- [1] S. CHANDRASEKHAR, *Radiative Transfer*, New York Dover.
- [2] B. DUBROCA, J. FEUGEAS, *Étude théorique et numérique d'une hiérarchie de modèles aux moments pour le transfert radiatif*, Academie des Sciences Paris Comptes Rendus Serie Sciences Mathématiques, 1999
- [3] M. GONZÁLEZ, E. AUDIT, P. HUYNH, *HERACLES: a three-dimensional radiation hydrodynamics code*, 2007
- [4] D. MIHALAS AND B.W. MIHALAS *Foundations of radiation hydrodynamics*, Oxford University Press, 1984
- [5] T. PADIOLEAU, P. TREMBLIN, E. AUDIT, P. KESTENER, S. KOKH *A high performance and portable all-Mach regime flow solver code with well-balanced gravity. Application to compressible convection*, submitted

**Hélène BLOCH**, Maison de la Simulation, CEA, CNRS, Univ. Paris-Sud, UVSQ, Université Paris-Saclay, 91191 Gif-sur-Yvette

`helene.bloch@cea.fr`

**Pascal TREMBLIN**, Maison de la Simulation, CEA, CNRS, Univ. Paris-Sud, UVSQ, Université Paris-Saclay, 91191 Gif-sur-Yvette

`pascal.tremblin@cea.fr`

**Edouard AUDIT**, Maison de la Simulation, CEA, CNRS, Univ. Paris-Sud, UVSQ, Université Paris-Saclay, 91191 Gif-sur-Yvette

`edouard.audit@cea.fr`

**Matthias GONZÁLEZ**, AIM, CEA, CNRS, Université Paris-Saclay, Université Paris Diderot, Sorbonne Paris Cité, UMR7158 91191 Gif-sur-Yvette

`matthias.gonzalez@cea.fr`